



# Primer

## LS-60C T2

### High spin washers

#### T2 CONTROL

User friendly and totally programmable 7" USB Connection. Online platform free of charge for programming, telemetry, data analysis...thanks to the IoT Videos on display (ads, instructions, etc.)  
37 languages  
8 dosing signals as standard

#### G FACTOR

High G-Factor: G-FACTOR 500 (11 - 18 kg), for 450 (22 - 80 kg) and 350 (100 - 120kg).  
It reduces the residual moisture.

#### CONNECTIVITY

**PRIMERLINK** - Standard and free IoT connectivity.  
Remote technical service.  
Management for laundries: OPL and COIN.  
Remote payment: **App PRIMER LAUNDRY** (mod. LS-11 up to LS-45C).

#### EFFICIENCY

Optimal KG.  
Intelligent consumption: automatic adjustment of water and soap consumptions (standard).  
Water Recovery tanks ready: **SAVETANK & SAVETANK XL**.  
Low water consumption.

#### VERSATILITY

Make to order: customisation.  
OPL < > COIN (mod. LS-11 up to LS-45C).  
Electric < > Hot water.  
Drain valve < > Pump (LS-11-14).  
Wet Cleaning.

#### ERGONOMICS

Easy opening/closing system for door lock.  
Biggest door diameters:  
• Ø 373 (11, 14 kg)  
• Ø 460 (18, 22, 28 kg)  
• Ø 560 (35, 45, 60, 80 kg)  
• Ø 700 (100, 120 kg)

#### EASY MAINTENANCE

Hinged control panel: easy and ergonomic access.  
Technical menu: statistics for technicians.

#### OTHERS

Grey skinplate outer casing.  
Drum and tub in stainless steel AISI 304.  
Detergent dispenser with 4 compartments.  
Electronic control of imbalance with frequency control.  
LOADING AID feature: water and rotation control.  
CB and WRAS approved product. Option ETL.  
REG4 standard certified by KIWA.




#### OPTIONS

- License IoT - Primer Link
- DQ-2 Dosing pump kit. 2 pumps with guide support.
- Extra detergent dosage DB-1
- Double drain kit LS-60C/80C
- Ready for SAVETANK XL conn. 1" for washers LS/RS-60C/80C
- Normally closed valve LS-60C/80C
- Double tilt LS-60C/80C. Compatible with the weighing system.
- Front tilt LS-60C/80C. Compatible with the weighing system.
- Water inlet hose LS-60C/80C (one per water intake)
- Weighing system LS-60C/ 80C/ 100C / 120C. Incl. kit 6 extra dosing signals
- 6 extra dosing signals card LS-60C/80C/100C/120C
- Reversible door: reverse door opening
- Steam kit LS-60C/80C
- Double heating E + S LS-60/80
- Stainless steel outer casing LS-60C
- Kit watermark Australia
- 440 V III No N 50/60 Hz LS-60C (maritime)
- 230 V III 50/60 Hz for LS-60C

DRUM	UNIT.	LS-60C T2	
Capacity 1/9	Kg	65	
Capacity 1/10	Kg	59	
Volume	l	590	
Diameter	mm	1.048	
Depth	mm	680	
GENERAL DETAILS			
Washing speed / Spining speed	r.p.m.	38 / 875	
G Factor	-	450	
Maximum force transmitted	KN	18 ±4,2	
Frequency-dynamic force	Hz	12,66	
Noise level	dB	< 70	
Coin laundry version	-	NO	
Double drain	-	OPT.	
Weighing system	-	OPT.	
Tilting door	-	OPT.	
DOOR			
Height center door / Height door	mm	1.170/810	
Diameter	mm	560	
POWER			
Motor	kW	15	
Electric heating power	kW	36	
Total electric power (electric model)	kW	39	
Total electric power (hw, steam model)	kW	15	
CONNECTIONS		E	HW/S
Tension 110V - I + N + T	Nº x mm² / A	-	-
Tension 230V - I + N + T	Nº x mm² / A	-	-
Tension 230V - III + T	Nº x mm² / A	3x25+T - 100A	3X6+T - 40A
Tension 400V - III + N + T	Nº x mm² / A	4x16+T - 63A	4x10+T - 50A
Steam inlet (Steam model)	inch	3/4"	
Maximum steam consumption (Steam model)	Kg/h	21	
Water inlet	inch	1"	
Water main pressuer	Kg/cm²	2-4	
Maximum water consumption*	l / h	598	
Drain	mm/inch	3"	
Drainage capacity	Lit/min	200	
DIMENSIONS / PACKING DIMENSIONS			
Net Width/Gross width	mm	1.420 / 1.600	
Net Depth/Gross depth	mm	1.433 / 1.595	
Net Height / Gross height	mm	1.890 / 1.930	
Net weight / Gross weight	kg	1.454 / 1.544	
Volume	m³	4,9	

\* Program number 20: LS-11 to LS-80C at 75% load / LS-100C and 120C at 100% load.





1. Soap dispenser
2. Emergency stop
3. USB port
4. Drain 1
5. Drain 2
6. Electric connection to liquid soap pumps
7. Electrical connection
8. Main switch
9. Auxiliar water inlet
10. Hot water inlet
11. Equipotential connection
12. Cold water inlet
13. Steam output
14. Liquid soap connection
15. Steam connection
16. Air intake
17. Ethernet port

		A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	CGY	CGZ
LS-60C	mm	1.420	1.433	1.890	810	560	760	1.050	1.563	323	1.475	1.710	1.817	508	912	367	595	720	845	1.040	1.267	160	1.353	608	1.500	348	830	820
	inch	55,91	56,42	74,41	31,89	22,05	29,92	41,34	61,54	12,72	58,07	67,32	71,54	20,00	35,91	14,45	23,43	28,35	33,27	40,94	49,88	6,30	53,27	23,94	59,06	13,70	32,68	32,28

